

Specification

Model : R0860BA

Description : 5000*8mm, 3528SMD LED, 60 LEDs/m, 12V DC, constant voltage,
non-waterproof flexible strip (UL)

Prepared by : _____

Checked by : _____

Standard Dept : _____

Approved by : _____

Issued Status: Draft Published

Specification

Product Name: Rhea Series

Model: R0860BA

Applications

Suitable for cove and contour lighting etc. in KTV, hotel, shopping mall, home, cabinet and so on.

Features

1. 3528SMD LED mounted;
2. Can be cut at the printed marks;
3. Certification: UL R94-V0 (UL file #E351381), RoHS ;



Installation

1. Easy installation with double-sided adhesive tape;
2. Many installation and fixing options available with the minimum bending diameter as 5cm[1.96in];

Warranty

2 years or 9,000 hours, whichever comes first.

Optical and Electrical Parameters:

P/N	LED Color	Color Temperature(K) Wavelength(nm)	Beam Angle (°)	Luminous Flux (lm/m)	CRI	Luminous Efficacy (lm/W)	Voltage (V DC)	Power (W/m)
R0860BA-UL	Warm White	3000	115	300	≥75	50	12	6
R0860BA-UL	Neutral White	6000	115	300	≥75	50	12	6
R0860BA-UL	Cold White	9000	115	300	≥75	50	12	6
R0860BA-UL	Red	620-625	115	138	--	23	12	6
R0860BA-UL	Green	520-530	115	240	--	40	12	6
R0860BA-UL	Blue	465-470	115	66	--	11	12	6
R0860BA-UL	Yellow	585-590	115	105	--	18	12	6

Others:


P/N	LED Color	Standard Length		Max. Length		LED Qty (pcs/m)	Operating Temperature		Storage Temperature		IP Grade
		(m)	(in)	(m)	(in)		(°C)	(°F)	(°C)	(°F)	
R0860BA-UL	White	5	196.85	5	196.85	60	-25~+6	-13~14	-25~+7	-13~15	IP33
R0860BA-UL	Red						0	0	0	8	
R0860BA-UL	Green										
R0860BA-UL	Blue										
R0860BA-UL	Yellow										

Notes:


- ① Testing environment temperature: 25±2℃ [77±3.6°F];
- ② The above data are typical values; the actual data of each single product could differ from the typical values. The data subject to change without prior notice;

Profile Drawings:

Unit: mm [in]



Packaging Diagram:



Packaging Information:

- 1. 5m [196.85in] per reel, 40 reels per outer carton;
- 2. Outer Carton: 45*25*25.6 cm=0.0288 (1±10%) CBM [17.72*9.84*10.08in]
- 3. Net Weight (N.W): 2.4 (1±10%) kg [5.291 (1±10%) lb];
- 4. Gross Weight (G.W): 5.4 (1±10%) kg [11.905 (1±10%) lb];
- 5. The actual packed quantity and weight subject to change without prior notice.